Product safety note: Components marked by the ⚠ symbol on this schematic have special characteristics important to safety. When replacing any of these components, be sure to use the parts specified in the parts list.

Video Board 800 — Red Video Amp. — Green Video Amp. — Blue Video Amp. — Beam current Feedback — CRT — ARC PROTECT — Auto Bias (V Sync ABA) — Beam Current Buffer — Auto Bright — B+G+R=S — 127V TC8 — TC2 Red, TC5 Green, TC 3 Blue — TC 10 — TC 6 — SOCKET BOARD CONNECTOR (TC) 206

Controls XRC5346A 241 — Ro Go Bo — BBL — +AEN +12V -ABL TTL MGAIN — RIN RR GIN GR BIN BR

Horizontal Size — Vertical Size — Vertical Raster Position — Horizontal Position — Master Gain — Remote Control PCB 490

LA7838 Vertical Deflection 377 — HEAT SINK 378 — Ramp Reset One Shot — Ramp Gen. — V. size Control 50/60Hz — Vert. Drive — Vert. Out — Thermal Protection — Retrace Booster Drive

Vertical Linearity Circuit — DECREASES TOP AND BOTTOM VERT. SIZE. — INCREASES TOP AND BOTTOM VERT. SIZE.

LA7851 — VERTICAL V+ — ± SYNC INPUT — VERTICAL OSCILLATOR — VERTICAL OSC. O/S — V Ref. — X-RAY PROTECT — Horizontal SYNC INPUT — PICTURE POSITION O/S — DELAYED SYNC O/S — SAW TOOTH GENERATOR — MULTIPLIER BIAS — HORIZONTAL OSCILLATOR DISCHARGE — VERT. OSC. — V. osc. ADJ. — comp. — H. V+

XRC5184 — INPUT ERROR AMP. — +15V +17V INPUT — Over Voltage Protect INPUT — CONTROL & FAULT SENSE — 4uS DELAY COMP. — Rx Osc. Cx — OUTPUT Current SENSE DRIVE — +7.5V REF. — V-

Video Board 800 — Fil. Fil. Rtn. Screen — FOCUS EHT — TC11 TC12 — FLYBACK TRANSFORMER — EHT — FOCUS — SCREEN — Beam Current — Horizontal Drive Transformer CPT1505 — CPT1516 — VERTICAL DEFLECTION YOKE — Horizontal Raster Adj. 150Ω 1/2W — CPT1538 12mH

2SC4159 — 2SC5690 — 2SA1371E — 2SC3467 — V RAS. POS. 0 TO 7 VDC — 2SA 1371 — IRF520 — CPQ1304

LM324 — LM393 — LM339 — LM392 — 7812 — 7810 — MPSA64 — CPR0432 100kΩ@25°C — CPR0434 Black Wire. — Beam Current Limiter Circuit. — Inrush Current Limit — Relay 200V.5A — 3A Fuse — Degaussing Connector — .093" pins — .093" pin — 230VAC INPUT

HORIZONTAL WIDTH CONTROL — Parabolic Pincushion Correction — -Linear Pincushion Correction — Blooming correction. — H. Linearity coil — HORIZONTAL YOKE — HORIZONTAL WIDTH DRIVE — High Temperature Or Excessive Beam Current, Monitor Shut Down Circuit.

VERTICAL BLANKING — HORIZONTAL BLANKING — VIDEO GAIN LINE — PN2907A — PN2222A (CPQ1322) — PN2222 — PN2222 (CPQ1302)

J PRA 111 — I PRA 416 — J PRA PINS: 3,10,15, & 19

CAUTION! POWER SUPPLY VOLTAGES REFERENCED FROM V-. SCOPE GND MUST NOT BE CONNECTED TO GND AND V- AT THE SAME TIME.

RED INPUT — GREEN INPUT — BLUE INPUT — VERTICAL SYNC — HORIZONTAL SYNC

Measurements are taken with a white screen. Hs - 5uS/div. Vs - 2mS/div.

LEGEND

No	BOARD PART No.
LTR.No	PART No. ON PRA.
X	PRA PIN No.
X-Y V	X-Y VDC (DC VOLTAGE RANGE, USING A DMM. USE V. or H. SYNC.
X-Y VDC Sync. Vp-p TP-REF. WAVEFORM	AC VOLTS TEST POINT Peak to Peak ASS. REF. Measured with scope

CERONIX 13350 New Airport Road, Auburn, California 95602

SCALE NONE	DATE & REV.	4/10/96-E1	3/24/99-E5
DRAWN BY: F. H.	2/18/92	9/30/96-E4	03/06/02-E8

CERONIX Model 1493-VGA, 1493-SVGA

CERONIX PART NO. CPA4200, CPA4252